

GIULY® SL

design Mariano Moroni

PATENTED

MATERIAL: Super slim heating body in painted mild steel.

FIXING KIT:

Brackets, airvent, hexagonal tool, plugs and screws suitable for use on compact or hollow brick, installation notice. The fixing kit is compliant with VDI 6036 norm, class 4.

VALVE KIT INCLUDES:

Valves kit Fittings for copper pipe (\emptyset 12/14/15) Fittings for multilayer pipe (\emptyset 16 x2)

PRODUCT CERTIFICATES



AWARD





PACKAGING:

The radiator is protected by a film in polyethylene and with a carton box. Use and maintenance notice included.

PAINTING PROCESS:

Painted with ecological epoxy. (Certificate DIN 55900-1,-2). Thermal outputs certified in accredited laboratories in compliance with European norm EN442.

COLORS:

Radiators and accessories: standard white R01 color. For other colors see color chart.

P. max: 5 bar

T. max: 110° C

Available for central heating systems

Connections: n° 2 x G 1/2" - n° 1 x G 1/2"

















H [mm]	A [mm]	B [mm]	I (*) [mm]		
1200	218	222	400		
1590	218	362	400		
1750	229	381	505		
1,20	225	501	505		

GIULY® SL

Art. Nr	Height	Width	Pipe Centres	Dry Weight	Surface	Water Content	Thermal output Watt		Exponent n
	H [mm]	L [mm]	l [mm]	[Kg]	[m ²]	[lt]	∆t = 50°C	∆t = 30°C	
3540806100222	1200	520	400	16	0,90	0,90	521	274	1,2603
3540806100223	1590	520	400	20	1,16	1,16	714	377	1,2518
3540806100225	1750	620	500	26	1,50	1,50	900	467	1,2849

Art. Nr. are referred to WHITE R01 color version.

The Art. Nr. is inclusive of VALVE AND HOLDER.

CLASSIC LINE

EXTRASLIM®