GLORIA 22

FI FCTRIC









MATERIAL:

- Ø 30 mm collectors in painted mild steel.
- Ø 22 mm horizontal heating elements in painted mild steel.
- · Heat transfer fluid.

FIXING KIT-

Brackets, hex key, airvent, dowels and screws suitable for use on solid walls or perforated bricks, assembly instructions.

The fixing kit is compliant with VDI 6036 norm, class 4.

The radiator is protected by recyclable cardboard box. User notice included.

PAINTING PROCESS:

Painted with ecological epoxy powders (Certificate DIN 55900-1,-2).

See color chart.

CERTIFICATES





FEATURES

Class protection: CLASS 1

Minimum ingress protection: IP 44

Wire lenght: 1200 mm with Schuko plug

Power supply: 230Vac 50Hz (with WiFi digital thermostat or PLUS)

Power supply: 230Vac 50/60Hz (with ECO DESIGN digital thermostat)

Seasonal energy efficiency η_s : 51,6% (with WiFi digital thermostat)

Seasonal energy efficiency η_s : 49,5% (with PLUS digital thermostat)

Seasonal energy efficiency $\eta_{s} :$ 50,5% (with ECO DESIGN digital thermostat)

ELECTRICAL ONLY

With WiFi digital thermostat

With PLUS digital thermostat

With ECO DESIGN digital thermostat

THERMOSTAT FINISH

WiFi version:
- WHITE on color radiators: R01 White, R02 Traffic White, T11 Matt White and F20 Milky; - CHROMED on all other colors

PLUS version:


WHITE on color radiators: R01 White, R02 Traffic White, T11 Matt White and F20 Milky;
 DARK GREY on all other colors.

- ECO DESIGN version:
 WHITE on color radiators: R01 White, R02 Traffic White, T11 Matt White and F20 Milky;
- BLACK on color radiators: R13 Jet Black e T01 Matt Black;
- CHROMED on all other colors.



Cordivari ErP electric radiators are characterised by high efficiency. These models comply with EU Regulation 2024/1103. The seasonal energy efficiency of these fixed electric space heating appliances, with nominal Thermal output >250 W, is over 46% in all models. Each of the ErP electric radiators is equipped with at least electronic temperature control, window opening detection, weekly programming and stand-by power consumption <0.5 W (or 2.0 W in Wi-Fi mode, where applicable).

HOW TO PLACE ELECTRIC RADIATORS



The national rules on installing electrical equipment in the bathroom must be scrupulously respected. The electric radiators must be always installed outside zone 1 and 2.


In particular the electric switch and control elements must be mandatorily located in zone 3, in order that no electrical control center is accessible to a anyone using the shower or bath.


INCLUDED





Remote control of PLUS digital chrono-thermostat


Remote control of PLUS digital chrono-thermostat functioning














(*) Pipe center (I) measure of the fixing kit

O The total height has to be calculated considering the thermostat height

DIGITAL THERMOSTAT WIFI O P AppStere

GLORIA 22 ELECTRIC WIFI

Height	Width	Fixing kit center distance	Art. nr.	Output	Weight
[mm]	L [mm]	I [mm] (*)	R01 White	[Watt]	[Kg]
790	430	400	3581666100036	400	10
1150	580	550	3581666100037	700	17
1500	580	550	3581666100038	900	22
1750	580	550	3581666100039	1200	25

Technical specification of the WiFi thermostat, see our range of digital thermostats



REMOTE CONTROL
INCLUDED
INCLUDED

GLORIA 22 ELECTRIC PLUS

Height	Width	Fixing kit center distance	Art. nr.	Output	Weight
[mm]	L [mm]	I [mm] (*)	R01 White	[Watt]	[Kg]
790	430	400	3581666100040	400	10
1150	580	550	3581666100041	700	17
1500	580	550	3581666100042	900	22
1750	580	550	3581666100043	1200	25

Technical specification of the PLUS thermostat, see our range of digital thermostats



GLORIA 22 ELECTRIC ECO DESIGN

Height	Width	Fixing kit center distance	Art. nr.	Output	Weight
[mm]	L [mm]	I [mm] (*)	R01 White	[Watt]	[Kg]
790	430	400	3581666100011	400	10
1150	580	550	3581666100012	700	17
1500	580	550	3581666100013	900	22
1750	580	550	3581666100014	1200	25

Technical specification of the ECO DESIGN thermostat, see our range of digital thermostats

The codes shown in the table refer to the R01 White color models