## ROSY PRO BADEN

The ventilation bathroom radiator



#### Specifications:

ROSY PRO BADEN is the new high-performance radiator of Cordivari Design, designed for the heating systems with heat pump or low temperature. The radiator uses a ventilation system with brushless DC inverter motor that guarantees comfort and high performances. Standard supplied with towel bars in 3 different configurations.

#### Material:

Painted carbon steel.

#### Fixing kit:

The fixing kits with screws and dowels suitable for compact wall or hollow bricks. For a correct installation please always refer to the assembly instructions. Packaging:

The radiator is protected by recyclable carton box.

### Painting process:

Painted with ecological epoxy powders (Certificate DIN 55900-1,-2). Colors:

Standard color White RAL 9016-R02.

#### **Control electronics**

Stand-alone control electronics for the management and control of the radiator.

**EUROPEAN** 

WARRANTY

 $(\epsilon)$ 

DC Brushless ventilator in low voltage 24Vdc.

Adaptor AC/DC 220V- 24 Vdc 30 W IP20 plug typ C with connection wire length between adaptor AC/DC and radiator 1400 mm. Minimum ingress protection: IP 24. Class protection: Class II.

#### SMART CONTROL operating mode

- Auto: the fan speed is adjusted automatically according to the flow temperature value read by the probe positioned on the radiator. The algorithm will choose whether to switch off, modulate or push the fan to maximum speed. The display always shows the current operating status of the decorative radiator.
- Manual: The user can select up to 4 fan speeds via the function buttons, independent of the flow temperature values. From the display you can always see the current operating status of the radiator.

### 

# ROSY PRO BADEN

The ventilation bathroom radiator



The national rules on installing electrical equipment in the bathroom must be scrupulously respected. The electric radiators must be always installed outside zone 1 and 2.

In particular the electric switch and control elements must be mandatorily located in zone 3, in order that no electrical control center is accessible to anyone using the shower or bath.

### **BADEN** ACCESSORIES



ZONE 3

R 0.6 m

Positioning of accessories ROSY PRO BADEN					
н	H1	H2	H3		
[mm]					
1220	625	825	1125		
1420	625	870	1325		
1620	625	925	1425		
1820	625	925	1525		
2020	625	925	1625		



## ROSY PRO BADEN

		PRO BADEN 1	PRO BADEN 2	PRO BADEN 3
Height H [mm]	Width L [mm]	Art. nr.	Art. nr.	Art. nr.
1220	389	3610456101292	3610456101298	3610456101304
	445	3610456101293	3610456101299	3610456101305
	501	3610456101294	3610456101300	3610456101306
1420	389	3610456101295	3610456101301	3610456101307
	445	3610456101296	3610456101302	3610456101308
	501	3610456101297	3610456101303	3610456101309

Article numbers in the table refer to models in color WHITE RAL 9016-R02 and connection V1.

SUPPORT - ACCESSORIES

HEATING TERMINALS